

Bonus Air 12

AIR TO WATER HEAT PUMP

RATED VOLTAGE/PHASE/FREQ:380-415V/3N~/50Hz

MOISTURE RESISTANCE: IPX4

ELECTRICAL SHOCK PROOF: I

***RATED HEATING CAPACITY: 11.0kW**

****RATED HEATING CAPACITY: 9.9kW**

RATED COOLING CAPACITY: 7.1kW

***RATED HEATING POWER INPUT: 2.5kW**

****RATED HEATING POWER INPUT: 3.8kW**

RATED COOLING POWER INPUT: 3.0kW

***RATED HEATING CURRENT INPUT: 4.17A**

****RATED HEATING CURRENT INPUT: 6.01A**

RATED COOLING CURRENT INPUT: 4.73A

MAX. POWER INPUT: 4.6kW

MAX. CURRENT INPUT: 7.2A

WATER PRESSURE DROP: 21kPa

WATER FLOW RATE: 1.7m³/h

REFRIGERANT/PROPER INPUT: R410A/1.65kg

NOISE: 52dB(A)

NET WEIGHT: 118kg

OPERATION PRESSURE(LOW SIDE): 2.1MPa

OPERATION PRESSURE(HIGH SIDE): 4.4MPa

FACTORY NUMBER: ON THE BAR CODE

MAKING DATE: ON THE BAR CODE

***HEATING:AMBIENT TEMP.(DB/WB):7°C/6°C**

WATER TEMP.(IN/OUT):30°C/35°C

****HEATING:AMBIENT TEMP.(DB/WB):7°C/6°C**

WATER TEMP.(IN/OUT):50°C/55°C

COOLING :AMBIENT TEMP.(DB/WB):35°C/24°C

WATER TEMP.(IN/OUT):10°C/7°C

DESIGNED AND DEVELOPED
BY ES NORD, SWEDEN
ENERGI SPARDIREKT NORD AB
KOLSTAVAGEN 31, 19591
MARSTA, SWEDEN

